

MATERIAL SAFETY DATA SHEET

Document Number MSDS-HTP-014

SECTION 1: NAME AND PRODUCT

Name:

SELEE Corporation

Address:

700 Shepherd Street
Hendersonville, NC 28792 U.S.A.

Product Name:

SELEE ZTA

Product Type:

Ceramic Filter

Contact:

Safety & Environmental Compliance Officer

Emergency Telephone Phone Number:

(828) 697-2411
(800) 438-7274

Telephone Number for Information:

(828) 697-2411
(800) 438-7274

Date Prepared:

31 Oct 06

Date Superseded:

04 Oct 05

Revision:

5

SECTION II: REGULATED INGREDIENTS*

Non-hazardous fired ceramic material, containing refractory ceramic fiber

SECTION III: HAZARD IDENTIFICATION

Inhalation:

Minimal inhalation hazard of particles.

Eyes/Skin:

Abrasion hazard.

Ingestion:

Unlikely

SECTION IV – HEALTH, FIRST AID AND MEDICAL TREATMENT

Inhalation:

Health Hazards (Acute and Chronic):
Avoid inhaling dust. Treat as nuisance dust.

Emergency and First Aid Procedures:
Treat as nuisance dust. Remove to fresh air

Ingestion:

Health Hazards (Acute and Chronic):
N/A

Emergency and First Aid Procedures:
N/A

Skin:

Health Hazards (Acute and Chronic):
Abrasive, recommend wearing protective equipment

Emergency and First Aid Procedures:
Wash with soap and water



700 Shepherd Street, Hendersonville, N.C. 28792 U.S.A.
(828) 697-2411 (800) 438-7274 Fax: (828) 693-1868

Eye: Health Hazards (Acute and Chronic):
Particle may enter eye

Emergency and First Aid Procedures:
Flush eye with water. See doctor if irritation proceeds

Other Potential Risks: Health Hazards (Acute and Chronic):
N/A

Emergency and First Aid Procedures:
N/A

Health Rating: **Health Hazard Rating Explanation:**

0	0 – Normal Material	2 – Hazardous	4 – Deadly
	1 – Slightly Hazardous	3 – Extreme Danger	

SECTION V – FIRE AND EXPLOSION HAZARD DATA

Flash Point: N/A (Method Used): N/A Flammable Limits:
LEL: N/A UEL: N/A

Extinguishing Media: Not flammable, will not support combustion

Special Fire Fighting Procedures: N/A

Explosion Potential: N/A

Fire Rating: **Fire Hazard Rating Explanation:**

0	0 – Will Not Burn	3 – Below 100°F (38°C)
	1 – Above 200°F (93°C)	4 – Below 73°F (23°C)
	2 – Below 200°F (93°C)	

SECTION VI – ACCIDENTAL RELEASE

Steps to be Taken in Case of Leaks or Spills:
Sweep up and dispose of in accordance with FEDERAL, STATE and LOCAL REGULATIONS.

SECTION VII – STORAGE, HANDLING AND USE PROCEDURES

Normal Storage and Handling:
When storing keep dry. Do not use wet filter. Avoid dust generation.

Normal Use:
Keep dry

SECTION VIII – PERSONAL PROTECTION INFORMATION

Respiratory Protection: For dust concentrations below the applicable exposure level, PPE is not required. If dust concentration levels are above the applicable exposure levels follow the requirements of OSHA 1910.134.

Ventilation: General and local exhaust ventilation, engineering controls, and good housekeeping practices are recommended keeping dust concentrations below the permissible exposure limits.

Protective Gloves: Recommended to prevent skin irritation.

Eye Protection: Safety Goggles

Other Protective Clothing and Equipment: Dust suppressing control technologies are effective means of minimizing airborne dust concentrations.

SECTION XVI – ADDITIONAL INFORMATION

Special Rating Explanation (If Applicable).

Oxidizer	Oxy	Alkali	ALK
Acid	ACD	Corrosive	COR
Use No Water	NW	Radiation Hazard	R

NAIF = No Applicable Information Found

N/A = Not Applicable